# **Material Safety Data Sheet**

MSDS REVISION DATE: Jan.7th, 2021 Report number:YDC20210102

Company: The Mani Club Limited

1a Warren arms place

Albert avenue

Stapleford

NG98BW

## Chemical Product and Company

Identification

Product name: Builder Gel

Product number: 137D

Product type: Ultraviolet UV Gel

Product type- Nail Paint

2. Ingredients

CAS NO.	Concentration WT%			
25133-97-5	68-78			
101-43-9	17-25			
58817-05-3	3-7			
12001-26-2	0-3			
following:				
16423-68-0	0-2			
1333-86-4	0-2			
7727-43-7	0-2			
1934-21-0	0-2			
12240-15-2	0-2			
12001-26-2	0-3			
	25133-97-5  101-43-9  58817-05-3  12001-26-2  following:  16423-68-0  1333-86-4  7727-43-7  1934-21-0  12240-15-2			

3. Emergency Overview

Physical state: Liquid HEALTH: 1\*

Color: Colors with gitter FLAMMABILITY: 2
Odor: light PHYSICAL HAZARD: 1

Personal Protection: See Section 8

WARNING: HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.DO NOT SPRAY. DO NOT

HEAT.MAY CAUSE ALLERGIC SKIN REACTION.CAUSES EYE,

SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, Inhalation, Eyes

**Potential Health Effects** 

Skin contact: Contact skin will cause irritation.

Eye contact: Contact with eyes will cause irritation.

#### 4. First aid measures

Inhalation: Remove to fresh air. If symptoms develop and persist,

get medical attention.

**Skin contact:** Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Wash clothing before reuse. Get immediate medical

attention if symptoms occur.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Get

medical attention immediately

#### .5. Fire-fighting measures

Flash point: 105°C

Autoignition temperature: Not available

Flammable/Explosive limits-lower %: Not available Flammable/Explosive limits-upper %: Not available

**Extinguishing media:** Foam, dry chemical or carbon dioxide. **Special fire fighting procedures:** Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Irritating organic vapors. Toxic fumes.

#### 6. Accidental release measures

Environmental precautions: Remove sources of ignition.
Prevent product from entering drains or open waters.
Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent. Store in a partly filled, closed container until disposal.

#### 7. Handling and storage

**Handling:** Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. DO NOT heat or spray. Use only with adequate ventilation. Refer to Section 8. Use only in area provided with appropriate exhaust ventilation. **Storage:** For safe storage, store at or below 26°C (80°F). Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. **Incompatible products:** Refer to Section 10.

#### 8. Exposure Controls/Personal Protection

Engineering controls: Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

Respiratory protection: Use COSHA approved respirator if there is potential to exceed exposure limit(s). If this material is handled at elevated temperatures or under mist forming conditions, without engineering controls, a COSHA approved respirator must be used. Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin contact. Neoprene gloves.

**Eye/face protection:** Safety goggles or safety glasses with side shields. In a splash hazard environment, chemical goggles should be used in combination with a full face shield.

#### 9. Physical and Chemical Properties

Physical state: Liquid
Odor: light
Vapor pressure: Not available
Boiling point/range: Greater

than 93°C (200°F)

Melting point/range: Not available Specific gravity: 1.10
Vapor density: Not available Evaporation rate: Not

available

Solubility in water: Slight Partition coefficient (n-

octanol/water): Not available

VOC content: Total volatiles 0.80 %

#### 10.Stability and Reactivity

Stability: Stable under normal conditions of storage and use.

Hazardous polymerization: May occur.

Hazardous decomposition products: Oxides of carbon. Oxides

of nitrogen. Dimethylamine. Irritating organic vapors.

Incompatibility: Strong acids. Strong oxidizing agents. Bases. Conditions to avoid: Heat, flames, sparks and other sources of

ignition. Do not heat above 26°C(80°C).

### 11.Toxicological Information

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	COSHA Carcinogen
Acrylates Copolymer	NO	NO	NO
CYCLOHEXYL METHACRYLATE/ETHYLHEXYL METHACRYLATE COPOLYMER	NO	NO	NO
Ethylhexyi Dimethyl PABA	NO	NO	NO

#### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs	
Acrylates Copolymer	No Records	
CYCLOHEXYL METHACRYLATE/ETHYLHEXYL METHACRYLATE COPOLYMER	No Records	
Ethylhexyi Dimethyl PABA	No Records	

This product is free solvent. The general damage is contact stimulation; excessive or repeated contact may stimulate skin; at the first beginning and long time short distance contact may stimulate eyes. The main irritant is acrylic esters.

#### 12. Ecological Information

Ecological information: Not available

#### 13.Disposal Considerations

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to

P.R.C, province and local governmental regulations.

ECE hazardous waste number: Not a RCRA hazardous waste.

### 14. Transport Information

The shipping classifications in this section are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

P.R.C Department of Transportation Ground:

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None

Packing group: None

International Air Transportation (ICAO/IATA): Not available

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None

Packing group: None

Water Transportation (IMO/IMDG): Not available

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None

Packing group: None Marine pollutant: None